

FLS-LED SERIES

The All-Purpose Flood/Area Light Now Ready For DLC 5

Introducing the new FLS-LED Series of Flood/Area Lights ideal for a variety of applications including parking lots, building facades, perimeter lighting and car dealerships.

- **Universal Mounting** – Yoke, Trunnion, Slipfit, Slipfit with Wall Adaptor, Mounting Arm for Round or Square Poles.
- **Rugged Design** – Die cast aluminum housing, polycarbonate lens.
- **Improved Efficacy** – Over 135 lumens per watt.
- **Easy to Install** – 1 meter power cord for easy connections, mounting system slides in place and is secured with 2 bolts.
- **Controls Ready** – Motion sensor, photocell are optional.
- **Dimmable** – 0 – 10V dimming is standard.



MOUNTING:



Slipfit



Slip Fitter
with wall adaptor



Trunnion



Yoke



Mounting Arm
(round or square poles)

TECHNICAL SPECIFICATIONS

	FL5S-LED100	FL5S-LED150	FL6S-LED230	FL8S-LED300	FL9S-LED400
Watts	105	142	228	296	396
Lumens	14,207	19,927	32,343	40,161	57,334
Efficacy (lm/W)	136	140	142	136	145
Operating Temp.	-40° C to +40° C				
Voltage	120-277V, 347V				
Colour Temp	5000K, 4000K				
Finish	Bronze				
Beam Distribution	T3, T5 optics				

FLS-LED Series
Launches End of
September 2020.
Contact Your RAB
Design Rep to
Learn More!

