













Lighting your way

Introducing the most innovative floodlight today, the RAB XFL.

Get ready to light up your world with our most comprehensive and customizable fixture yet. Our 50-year tradition of working with contractors to guide our process has led us to create and patent the XFL family. It's truly lighting your way, giving you more choices than ever when it comes to illuminating a space.

The XFL is the only floodlight on the market with field adjustable beam distribution, ensuring contractors get light exactly where they need it. Along with a host of other customizable features like colour temperature and a sturdy design built for extreme Canadian weather conditions, it's another innovation meant to help get the job done right the first time.



Some very bright highlights





Field Adjustable Beam Distribution

The XFL has the unique ability to tailor light patterns to your specific requirements with extra wide, wide, and medium-wide beam distribution. You'll always have the right solution and lighting precisely where you need it. Furthermore, we can quickly configure the narrow beam option for you at our factory.





Full Customization

Take advantage of three adjustable lumen and colour temperature options that will suit any project's need.



Efficient

Integrated photocell ensures that your customers have lighting when they need it without the use of timers.









Built Strong and Stylish

With an IP65 rating and a 7-year warranty, the XFL family is ready to work through extreme Canadian weather and more, all at an attractive price.









Ready for Any Situation

Thanks to 5 sizes, multiple mounting options, and universal voltage, the XFL is ready for any situation.



Get the perfect XFL for your next project.

To learn more or to place an order, call 1-800-268-0381, scan the QR code, or visit **rabdesign.ca/XFL**

Find the right XFL for your job



SPECIFICATIONS	XFL1-LED30A15	XFL2-LED60A35	XFL3-LED80A60	XFL4-LED150A100	XFL5-LED300A150
Input Power	35W Max 15W Min	60W Max 35W Min	80W Max 60W Min	150W Max 100W Min	300W Max 150W Min
Lumens	5250lm Max 2100lm Min	9000lm Max 4900lm Min	12000lm Max 8400lm Min	22500lm Max 14000lm Min	42000lm Max 21000lm Min
Efficacy	150 lm/W				
Voltage	120-347V				
Housing Finish	Bronze,* Custom Finish				
Housing Details	Die Cast Aluminum				
Lens Details	Clear Glass lens				
Mounting	Knuckle , Yoke (i	nclulded in box)	Slip fitter, Yoke (inclulded in box)		
Photocell	DC photocell			AC Twistlock Photocell with Shorting cap	
Operating Temp.	-40°C to +50°C				

^{*}Standard Configuration

Default Factory Setting: 4000K/Highest lumen setting/90°Beam/Photocell ON

Factory installed options include custom finishes and narrow beam distribution. Narrow beam options for XFL1/XFL2/XFL3/XFL4 are 35° (NEMA 5X5) and for XFL5 are 35° NEMA 5X5 or 20° NEMA 4X4.

Knuckle attached for XFL1/XFL2, Yoke and Mounting plate included in box Slipfitter attached for XFL3/XFL4/XFL5, Yoke included in box, 10kV Surge protection is standard.

STOCK CODE	DESCRIPTION
081829	XFL1-LED35A15-H-VK-VDW-BRZ-DIM-PC-FCM
081830	XFL2-LED60A35-H-VK-VDW-BRZ-DIM-PC-FCM
081831	XFL3-LED80A60-H-VK-VDW-BRZ-DIM-PC-FCM-SP10
081832	XFL4-LED150A100-H-VK-VDW-BRZ-DIM-PC-FCM-SP10
081833	XFL5-LED300A150-H-VK-VDW-BRZ-DIM-PC-FCM-SP10

LEGEND:

Fixture size/Wattage = XFL1/Max. 35W, Min 15W, XFL2/Max 60W, Min 35W, XFL3/Max. 80W, Min. 60W, XFL4/ Max. 150W, Min. 100W, XFL5/ Max. 300W, Min 150W VK = Colour Selectable 3000K/4000K/5000K VDW = Variable Distribution WIDE (Extra WIDE 90°, 7x6) (WIDE - 75°, 6x6) (Medium WIDE 55°, 5x5), BRZ = Bronze, DIM = 0-10V Dimming, PC = Photocell, FCM = Field Convertible Mounting, SP10 = 10kV Surge Protection



Get the perfect XFL for your next project.

To learn more or to place an order, call 1-800-268-0381, scan the QR code, or visit **rabdesign.ca/XFL**

