

VEKX-LED HIGH PERFORMANCE WALL LIGHT



FEATURES

- **Lumen & CCT selectable** with 120-347V input
- High efficiency fixture with 170 lm/W
- **Dark Sky Friendly** - No up light at zero tilt
- Adjustable head with Type III optics for precise lighting
- Tamper proof stainless steel hardware
- Standard DC Photocell for **dusk to dawn operation**
- Control options - PCLS and DHFS (Factory Installed)



IDEAL FOR



Perimeter
Lighting



Landscape
Lighting



Architectural
Applications

SPECIFICATIONS

| | VEKIX-LED30A15 | VEK2X-LED60A30 | VEK3X-LED90A60 |
|----------------|----------------------------------|-------------------|----------------------|
| Watts | 30/25/15 W | 60/45/30 W | 90/75/60 W |
| Lumens | 4700/3700/2500 lm | 9600/6600/5100 lm | 14000/11000/10000 lm |
| Efficacy | 170 lm/W | | |
| Operating Temp | -40°C to 40°C | | |
| Voltage | 120-347V | | |
| Colour Temp | 3000/4000/5000K (CCT Selectable) | | |
| Lens Details | Polycarbonate Lens | | |
| Housing | Die-cast Aluminum | | |
| Controls | DC Photocell, PCLS, DHFS | | |

