



FLEXILINE

Linear Architectural



The ultimate solution for highly versatile and adaptable lighting for indoor spaces. FLEXILINE offers unparalleled flexibility by enabling the user to effortlessly switch between direct/indirect light, different CCTs, and lumens. FLEXILINE offers multiple mounting options and unique shape configurations allowing for precise illumination tailored to any environment. Elevate your architectural designs with FLEXILINE and illuminate your vision with endless possibilities.


IDEAL APPLICATIONS

- ☒ Offices
- ☒ Boardrooms
- ☒ Hallways
- ☒ Receptions
- ☒ Condos

SPECIFICATIONS

	FLEX24- LED20A12	FLEX48- LED40A24	FLEX72- LED60A36	FLEX96- LED80A48		FLEX24- LED20A12	FLEX48- LED40A24	FLEX72- LED60A36	FLEX96- LED80A48
PERFORMANCE					CONSTRUCTION				
Light Output ¹	2700/1900/ 1600 lm	5200/4200/ 3400 lm	8100/5900/ 4600 lm	10400/7900/ 6100 lm	Housing	Extruded Aluminum			
	Lumen Selectable				Lens	Frosted Polycarbonate Lens			
Efficacy	136 lm/W				Weight	3.0lbs	4.5lbs	6.2lbs	8.2lbs
CCT	CCT Selectable - 3000K/3500K/ 4000K				AMBIENT OPERATING TEMPERATURE				
Up%-Down% Selection	0%-100%, 15%-85%, 30%-70%				-20°C to 45°C (-4°F to 113°F)				
Beam Distribution	120°				MOUNTING				
LED Lifetime (L80)	>100,000 Hrs				Suspension Mount - 6' power cable & air craft cable (Standard)				
CRI	85				Suspension Mount for T-grid, Surface mount, Wall mount				
ELECTRICAL					CERTIFICATIONS				
Wattage	20/15/12W	40/30/24W	60/45/36W	80/60/48W	cULus Listed for Canada and USA, per UL 1598, CSA C22.2 No. 250.0, DLC Standard & Premium				
Voltage	120-347V				CONTROLS				
Surge Protection	2kV as per IEC/EN61000-4-5				0-10V Dimming (Dim to Off)				
THD	<10%				Note: - All reported values were tested at 120V and 3500K and shown for the highest lumen setting. Default Setting: Highest wattage/ 4000K/ 100% Downlight ¹ Light output is 1300lm/ft for all fixture lengths. ² Connectors do not draw additional power, as they share the power supply with the fixture.				
Power Factor	>0.99								
Cord	Pre-installed 6' Power Cable (5x18 AWG)								
Daisy Chain ²	4A Max (Max. length of 40ft at 120V & 100ft at 347V)								

CREATE CONFIGURATIONS WITH EASE









Create any configuration of your choice with six different illuminated corner connector shapes.



ORDERING GUIDE

		H	VK		DIM	BLANK	
Fixture	Wattage	Voltage	Colour Temp.	Finish	Dimming	Mounting	
FLEX24	LED20A12	H - 120-347V	VK - CCT Selectable 3000K/3500K/ 4000K	WHT - White	DIM - 0-10V Dimming	BLANK - Suspension Mount	
FLEX48	LED40A24			BLK - Black			
FLEX72	LED60A36			BLK - Black		WM - Wall Mount	
FLEX96	LED80A48						

STOCK CODES		INCLUDED IN THE BOX	
083733	FLEX24-LED20A12-H-VK-WHT-DIM	6FT AIR CRAFT CABLES & SUSPENSION MOUNT HARDWARE	
083726	FLEX48-LED40A24-H-VK-WHT-DIM		
083727	FLEX72-LED60A36-H-VK-WHT-DIM		
083728	FLEX96-LED80A48-H-VK-WHT-DIM		
083729	FLEX24-LED20A12-H-VK-BLK-DIM		
083730	FLEX48-LED40A24-H-VK-BLK-DIM		
083731	FLEX72-LED60A36-H-VK-BLK-DIM		
083732	FLEX96-LED80A48-H-VK-BLK-DIM		

ACCESSORIES SOLD SEPARATELY					
083734	VK 90 DEGREE L CONNECTOR WHT		083737	VK 90 DEGREE T CONNECTOR WHT	
083864	VK 90 DEGREE L CONNECTOR BLK		083982	VK 90 DEGREE T CONNECTOR BLK	
083735	VK 60 DEGREE L CONNECTOR WHT		083738	VK 90 DEGREE X CONNECTOR WHT	
083985	VK 60 DEGREE L CONNECTOR BLK		083983	VK 90 DEGREE X CONNECTOR BLK	
083736	VK 120 DEGREE L CONNECTOR WHT		083739	VK 120 DEGREE Y CONNECTOR WHT	
083987	VK 120 DEGREE L CONNECTOR BLK		083986	VK 120 DEGREE Y CONNECTOR BLK	
083741	VK 1FT STRAIGHT CONNECTOR WHT		083743	CANOPY MOUNTING DISCS & CROSSBAR KIT WHT	
083988	VK 1FT STRAIGHT CONNECTOR BLK		083882	CANOPY MOUNTING DISCS & CROSSBAR KIT BLK	
083744	SURFACE MOUNT KIT WHT		083745	JUNCTION BOX COVER WHT	
083883	SURFACE MOUNT KIT BLK		083865	JUNCTION BOX COVER BLK	
083742	STRAIGHT FIXTURE CONNECTOR BRACKET (Required for row-mounting fixtures)		083746	T-GRID MOUNTING BRACKET	

- Note:**
- Please reach out to our Customer Success team for any inquiries about components needed to create your configurations.
 - The 1ft straight connector can be used in between two fixtures to create custom lengths.
 - Connectors have down LED boards only but can be used for both downlight and up-and-downlight configurations.


MAX AMPERAGE DRAW (A)				
	120V	240V	277V	347V
FLEX24-LED20A12	0.183	0.092	0.079	0.063
FLEX48-LED40A24	0.367	0.183	0.159	0.127
FLEX72-LED60A36	0.550	0.275	0.238	0.190
FLEX96-LED80A48	0.733	0.367	0.318	0.254

LUMEN MAINTENANCE		
L90	L80	L70
58,000 Hrs	110,000 Hrs	130,000 Hrs

Note: Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 calculations.

UPLIGHT - DOWNLIGHT LUMENS							
Model	Wattage (W)	0% Uplight - 100% Downlight		15% Uplight - 85% Downlight		30% Uplight - 70% Downlight	
		Uplight (lm)	Downlight (lm)	Uplight (lm)	Downlight (lm)	Uplight (lm)	Downlight (lm)
FLEX24-LED20A12	20	0	2700	400	2300	800	1900
	15	0	1900	300	1600	600	1300
	12	0	1600	200	1400	500	1100
FLEX48-LED40A24	40	0	5200	800	4400	1600	3600
	30	0	4200	600	3600	1300	2900
	24	0	3400	500	2900	1000	2400
FLEX72-LED60A36	60	0	8100	1200	6900	2400	5700
	45	0	5900	900	5000	1800	4100
	36	0	4600	700	3900	1400	3200
FLEX96-LED80A48	80	0	10400	1600	8800	3100	7300
	60	0	7900	1200	6700	2400	5500
	48	0	6100	900	5200	1800	4300


DIMENSIONS



	A	B	C	D	E	*F
2-FT	610mm [24.0in]	604mm [23.8in]	75mm [3.0in]	84mm [3.3in]	50mm [2.0in]	459mm [18.1in]
4-FT	1221mm [48.1in]	1215mm [47.9in]	75mm [3.0in]	84mm [3.3in]	50mm [2.0in]	1037mm [40.8in]
6-FT	1829mm [72.0in]	1823mm [71.8in]	75mm [3.0in]	84mm [3.3in]	50mm [2.0in]	1678mm [66.1in]
8-FT	2440mm [96.1in]	2434mm [95.8in]	75mm [3.0in]	84mm [3.3in]	50mm [2.0in]	2253mm [88.7in]


*DEFAULT DIMENSIONS - CAN BE ADJUSTED

FLEX-LED WALL-MOUNTED




ACCESSORIES DIMENSIONS


90 DEGREE L CONNECTOR




90 DEGREE T CONNECTOR




60 DEGREE L CONNECTOR




90 DEGREE X CONNECTOR




120 DEGREE L CONNECTOR




120 DEGREE Y CONNECTOR



1FT STRAIGHT CONNECTOR



JUNCTION BOX COVER




PHOTOMETRIC PLOTS

FLEX24-LED20A12

(4000K, 20W, DOWNLIGHT ONLY, MOUNTED AT 9 FEET)


LUMENS: 2642 LM MAX CALCULATED VALUE: 11.73 FC



FLEX48-LED40A24

(4000K, 40W, DOWNLIGHT ONLY, MOUNTED AT 9 FEET)


LUMENS: 5116 LM MAX CALCULATED VALUE: 22.62 FC



FLEX72-LED60A36

(4000K, 60W, DOWNLIGHT ONLY, MOUNTED AT 9 FEET)

LUMENS: 8187 LM MAX CALCULATED VALUE: 36.77 FC



FLEX96-LED80A48

(4000K, 80W, DOWNLIGHT ONLY, MOUNTED AT 9 FEET)

LUMENS: 10264 LM MAX CALCULATED VALUE: 45.39 FC

