

LFY4-LED

LINEAR VAPOURPROOF FIXTURE

Introducing our linear vapourproof LED fixture, designed for **versatility** and **durability** in demanding environments.

Developed using specialized techniques contributed by numerous contractors and distributors, the new linear vapourproof solution combines rugged construction with advanced features to deliver reliable, tailored illumination.





The LFY4-LED Linear Vapourproof Offers:



120-347V



Colour Temperature Selectable Universal Voltage

Lumen Adjustable



LFY4-LED

LINEAR VAPOURPROOF FIXTURE



Stainless Steel Clips Housing designed to avoid clips falling. Also, fewer clips required while maintaining NEMA 4X and IP66.



Wider Profile 4.6" wide to cover standard junction box.



Perfectly Flat Housing Back Leaves no gap with mounting surface.



Straightforward **Assembly** 2 Conduit entries at each end, and guide marks at the back for conduit entries.



Fewer Components Reducing the number of pieces making it easier to install.



Offset Driver Driver is offset from the center and comes with 1' long input cable.



Cover for CCT and Wattage Switches Prevents accidental changes to settings.



Quick Disconnect Detach housing and lens/LED board easily.

IDEAL FOR:

SPECIFICATIONS:

Food Processing & Storage

Live Stock Barns

Agricultural Applications

Industrial Applications

Underground Parking Garages

Warehouses

LED40A20

LED60A40

Efficacy: 144 lm/W 151 lm/W

9100 lm 6400 lm Lumens:

Housing: Polycarbonate

Colour Temp: 3500K/4000K/5000K

Controls: DHFS Motion Sensor





















