




# STRING LIGHTS

## STR-LED



STR10-LED130

Light up any job site with confidence using this rugged LED temporary string light, designed to perform in wet and demanding environments. Available in 100 ft length, STR features heavy-duty **16/3 AWG** cables and a **linkable design** that makes expanding coverage fast and effortless. Integrated **hanging hooks** enable quick, hassle-free installation, helping keep projects on schedule and worksites safely illuminated.

### IDEAL APPLICATIONS

- Construction Sites
- Walkways
- Access Paths
- Tunnels & Underpasses

### SPECIFICATIONS

| STR10-LED130                         |   |
|--------------------------------------|---|
| <b>PERFORMANCE</b>                   |   |
| Light Output per String              | 16000 lm (100 ft)                         |
| Light Output per Lamp                | 1600 lm                                   |
| Efficacy                             | 125 lm/W                                  |
| CCT                                  | 5000K                                     |
| CRI                                  | 80  |
| Beam Spread                          | 360°                                      |
| <b>ELECTRICAL</b>                    |   |
| Wattage                              | 130W                                      |
| Number of lamps per string           | 10 lamps                                  |
| Voltage                              | 120V                                      |
| <b>CONSTRUCTION</b>                  |   |
| Housing                              | Polycarbonate                             |
| Lens                                 | Frosted Polycarbonate - Dome Shaped       |
| Length per fixture                   | 100 ft                                    |
| Maximum linkable length              | 500 ft (5 Strings = 50 lamps )            |
| Cable                                | SJTW 16/3 AWG                             |
| Plug & Connector                     | 3 Prong NEMA 5-15P (Male and Female ends) |
| <b>ACCESSORY SOLD SEPARATELY</b>     |   |
| Polycarbonate Lamp Guard             |   |
| <b>AMBIENT OPERATING TEMPERATURE</b> |   |
| -40°C to 40°C (-40°F to 104°F)       |   |
| <b>CERTIFICATIONS</b>                |   |
| cETLus, IP65                         |   |



## ORDERING GUIDE

|              |               |          |                    |
|--------------|---------------|----------|--------------------|
| <b>STR10</b> | <b>LED130</b> | <b>A</b> | <b>5K</b>          |
| Fixture      | Wattage       | Voltage  | Colour Temperature |
| STR10        | LED130        | A - 120V | 5K - 5000K         |

| STOCK CODES |                   |
|-------------|-------------------|
| 084901      | STR10-LED130-A-5K |

## DIMENSIONS

