



SPR - 4" ROUND ALUMINUM POLE

The SPR pole is available from 8 feet up to 14 feet in height. The SPR pole can be used with single or multiple globe assemblies with the option of a post line ballast available up to 150 watt HPS or 100 watt MH ballast. The following fixtures can be used with the SPR pole, Gamma, Torchlight, Small Colonial, Medium Colonial, and the Coachman. Ideal for use in small courtyards, condominiums and apartment buildings.

POLE Extruded aluminum, with a 4" diameter and a 1/8" thickness. Pole has a powder coat paint finish.

BASE Cast aluminum base welded to the pole. Base is held in place with four .62" diameter anchor bolts that are to be set into a concrete pad.

ANCHOR BOLTS Four galvanized, .62" x 15" diameter, twelve inch long anchor bolts complete with nuts and washers.

BASE COVER Spun aluminum cover with a powder coat paint finish.

OPTIONS Hand hole with cover, 3" tenon.

FINISH Standard colours are black and bronze. For custom colours please consult factory.



Catalog Code

SPR

8, 10, 12, 14, 16 (FEET)

HEIGHT IN FEET

BRZ - BRONZE
BLK - BLACK
CC - CUSTOM FINISH

FINISH

***BH/H - HAND HOLE & COVER AT BASE**
H/H - HAND HOLE & COVER
3 - 3" TENON

OPTIONS

*STANDARD CONFIGURATION

FOR "H/H-HAND HOLE & COVER", PLEASE SPECIFY HEIGHT FROM THE TOP/BOTTOM

9.00" DIA. SPUN
ALUMINUM
BASE COVER

FOUR .62" X 15.00"
LONG ZINC PLATED
ANCHOR BOLTS.
COMPLETE WITH
NUTS AND WASHERS.

3" TENON AVAILABLE
FOR TOP OF POLE

8' TO 16'

0511

www.rabdesign.ca