Project: Type: Date: Notes:

4" Round Aluminum Pole

SPR



The SPR pole is available from 8 feet up to 14 feet in height. The SPR pole can be used with single or multiple globe assemblies with the option of a post line ballast available up to 150 watt HPS or 100 watt MH ballast. The following fixtures can be used with the SPR pole, Gamma, Torchlite, Small Colonial, Medium Colonial, and the Coachman. Ideal for use in small courtyards, condominiums and apartment buildings.

SPECIFICATIONS

	SPR
Pole	Extruded aluminum, with a 4” diameter and a 1/8” thickness. Pole has a powder coat paint finish.
Base	Cast aluminum base welded to the pole. Base is held in place with four .62” diameter anchor bolts that are to be set into a concrete pad.
Anchor Bolts	Four galvanized, 0.75" x 18" anchor bolts complete with nuts and washers.
Base Cover	Spun aluminum cover with a powder coat paint finish.
Options	Hand hole with cover, 3” tenon.
Finish	Standard colours are black and bronze. For custom colours please consult factory.

CATALOGUE CODE

SPR

HEIGHT IN FEET	8, 10, 12, 14, 16 (FEET)
FINISH	BRZ - BRONZE BLK - BLACK CC - CUSTOM FINISH
OPTIONS	*BH/H - HAND HOLE & COVER AT BASE H/H - HAND HOLE & COVER 3 - 3" TENON

*STANDARD CONFIGURATION

FOR "H/H-HAND HOLE & COVER", PLEASE SPECIFY HEIGHT FROM THE TOP/BOTTOM

