

## **CONTRAST LED - BY THORN**

The Contrast LED is a small compact flood light used to project light up to 30 meters away, yet can produce a variety of precise beam distributions using various accessories. Standard unit is with white LED'S available in cool white (6000K) or warm white (3000K), blue, red or green LED'S. Also available in RGB running on DMX. The Contrast LED can be used for almost any exterior lighting design, from illuminating a bridge, highlighting columns or to creating a dramatic effect on buildings.

**HOUSING** Die cast aluminum with a textured grey powder coated finish.

**LENS** 4mm clear tempered glass with a continuous gasket.

**LED'S** 54 LED'S for white, red, blue and green. 36 LED'S with the RGB version.

RGB OPTION RGB units that require special effects or synchronization needs the Spectra Memory box. Software not included. Maximum run for one Spectra Memory box is 300 metres with a maximum of 32 fixtures. If there is no special affect or synchronism between multiple fixtures an automatic sequence can be played by setting all DMX switches to zero.



**POWER SUPPLY** 120 volts remote mount.

**FINISH** Standard finish is a textured grey powder coated paint finish.

**OPTIONS** Visor, fixed louvre, adjustable anti-glare louvre, wire guard, semi-intensive prismatic glass, medium-wide refractor, semi-extensive prismatic glass, wide refractor, extensive prismatic glass, narrow refractor and super extensive prismatic glass.

## **Catalog Code**

## CONTRAST LED

86,6W 54 LED WHI/6000K 86,6W 54LED WHI/3000K 86,6W 54 LED BLU

60W,54 LED RED 86,6W 54LED GRN

LAMP 51,6W 54LED RGB DMX

REFRACTOR OPTIONS

R0 GL/FRS/S SINT - SEMI-INTENSIVE SYMMETRICAL

R0 GL/A/S SINT - SEMI-EXTENSIVE ASYMMETRICAL

R0 GL/A/EXT - EXTENSIVE ASYMMETRICAL

R0 GL/S/SXEXT - SUPER EXTENSIVE SYMMETRICAL

R0 LR1 - MEDIUM WIDE REFRACTOR

R0 LR2 - WIDE REFRACTOR

**R0 L3 - NARROW REFRACTOR** 

R0 GL CHROMAT - WARMER GLASS LEE FILTER 205 R0

WG - WIRE GUARD, RO LV - FIXED ANTI GLARE LOUVRE,

R0 LV/AJ - ADJUSTABLE ANTI GLARE LOUVRE

OPTIONS RO AGF - SPILL LIGHT CONTROLLER

R0 VS - VISOR C0/R0 AGS(X1) BARN DOOR

## **Dimensions**

