

HID BULLET WITH HOOD

The Bullet series is ideal for use in open areas for accent and up-lighting of trees, walls, signs and building facades. The hood and heat resistant tempered clear glass with silicone gasketing, provides watertight protection.

BALLAST HOUSING Two-piece, heavy die cast aluminum with side and bottom 1/2" conduit openings. Close out plugs included. Ballast housing has a powder coat paint finish.

BULLET Die cast aluminum with a powder coat paint finish.

HOOD Die cast aluminum with a powder coat paint finish, a heat treated tempered glass lens with silicone gasketing. Hood has a set screw for attachment to the bell.

MOUNTING ARM Heavy duty mounting arm with internal O-ring, locking teeth, and stainless steel screw. EZ Grip locknut matches fixture finish and can be adjusted with fingers, pliers or a screwdriver.

BALLAST All ballasts are Metal Halide Pulse start and are configured as follows, 70MH 120V NPF, 70MH 120V HPF QT and 100MH 120V HPF QT.

LAMP Lamps are not included. These fixtures are designed to take the following lamps, PAR38 Narrow Spot, Spot, Narrow Flood and Wide Flood, and ED17 lamps.



SOCKET Medium base 4KV pulse-rated socket with a nickle-plated screw shell and a spring-loaded centre contact.

FINISH Powder coat paint finish in the following colours Bronze, Black, White and Verde Green.

