



LFP16 LINE VOLTAGE PAR16

The LFP16 uses PAR16 lamps, with an integral glare shield and lens. Glare shield is fitted further down on the housing for ease of lamp replacement. Accepts up to 60 watts PAR16 lamp. The LFP16 is ideal for use in both commercial and residential lighting for landscape and highlighting architectural features. The LFP16 can also be used with any of our outdoor sensors.

HOUSING Rugged die cast aluminum housing. The housing also has a set screw for holding the glare shield in place. Housing has a powder coat paint finish.

GLARE SHIELD Rugged die cast aluminum. Housing and glare shield have a silicone gasket. Glare shield has a powder coat paint finish.

LENS Clear tempered glass siliconed in place to prevent water from entering the fixture.

MOUNTING ARM Heavy duty mounting arm with internal O-ring, locking teeth, and stainless steel screw. EZ grip locknut matches fixture finish and can be adjusted with fingers, pliers or a screwdriver.

SOCKET Medium base, porcelain.



LAMP Maximum wattage 60 watt PAR16. Lamp not included.

FINISH Powder coat paint finish available in White, Charcoal, Bronze and Verde Green.

Catalog Code

LFP16

A - BRONZE
B - BLACK
W - WHITE
VG - VERDE GREEN

FINISH

RAB
DESIGN



Dimensions

