

U/D - UP/DOWN LIGHT WALL MOUNT

The U/D is a 8" wall mounted cylinder used for direct illumination on walls or columns. The U/D can be used in either outdoor or indoor applications. The reflector provides 45 degree cut-off to the lamp. The U/D is ideal for a wide use in commercial, retail, hospitality and institutional applications.

HOUSING Made of extruded aluminum .188 wall thickness with a powder coat paint finish.

REFLECTOR Spun aluminum anodized.

SOCKET For Metal Halide the socket is a porcelain socket 4KV pulse rated with an enclosed screw shell and a spring loaded centre contact.

BALLAST HOUSING Sheet metal housing containing two ballasts with a powder coat paint finish.

BALLAST All ballasts are core and coil Tri-Tap. Available in 50, 70, 100 and 150 watts High Pressure Sodium and 50, 70, 100, 150 and 175 watts in Metal Halide. All ballasts are available in 120, 277 and 347 volts.

LAMPS All units are shipped complete with lamp.



HARDWARE All exterior hardware is made of stainless steel to ensure corrosion-free protection from the elements.

FINISH Powder coat paint finish. Standard colours are black, white, bronze and charcoal. For custom colours please consult factory.

GLASS LENS All units come with an upper and lower tempered glass lens. Glass lens are available as clear or frosted.



