

## P3RP PENDANT DOWN LIGHT

The P3RP is an 8" round cylinder, pendent mount fixture that is ideal for use in atruims, retail, hospitality and institutional applications. The reflector provides a 45 degree cutoff.

**HOUSING** Made of extruded aluminum .188 wall thickness with a powder coat paint finish.

**REFLECTOR** Spun aluminum anodized.

**SOCKET** For Metal Halide medium base 4KV pulse-rated socket with a nickle-plated screw shell and a spring-loaded centre contact. For compact fluorescent, the socket is injection molded with integral clips for lamp retention. Incandescent sockets are medium base 4KV pulse rated with a nickle-plated screw shell and a spring-loaded centre contact.

**ROD** Rigid conduit, standard length is 18 inches. Maximum length is 10 feet, for lengths over 3 feet a ball aligner is used to ensure the fixture hangs straight.

**HARDWARE** All exterior hardware is made of stainless steel to ensure corrosion-free protection from the elements.

**LAMPS** All HID units come complete with open rated lamps. For all compact fluorescent, units lamps are included. For incandescent units, lamps not included.



**BALLASTS** All HID ballasts are core and coil Tri-Tap available as 50, 70, 100 and 150 High Pressure Sodium and 50, 70, 100, 150 and 175 Metal Halide. Compact fluorescent ballasts are electronic 120, 277 and 347 available in the following wattages 26, 32 and 42 watt. Incandescent units are rated up to 250 watts.

**FINISH** Powder coat paint finish. Standard colours are bronze, black and white. For custom colours please consult factory.

**OPTIONS** Bottom lens, quartz restrike.



