

## P8RDL 42" BOLLARD

The P8RDL bollard is suitable for landscape and pathway lighting with glare free distribution. Ideal for use in shopping malls and commercial real estate.

**LOWER BODY** 8" round extruded aluminum (.125 wall thickness) that fits over base and secured with stainless steel screws. Body has a powder coat paint finish.

with vertical support ribs at 120 degrees. Louvres are angled at 25 degrees to provide glare free illumination. Louvres are secured to upper cast aluminum dome cap using the support ribs. To remove louvre assembly for re-lamping purposes undo set screws on louvre assembly and remove globe. Cast louvres and dome have a powder coat paint finish.

**OPTICS** Standard unit has clear globe, also available are prismatic, frosted, blue, red, green, white and amber. All units are type V distribution. Internal house shield is available as 90 or 180 degrees.

**BALLAST** All ballasts for Metal Halide are Tri-Tap 120,277,347 volts for 50, 70 and 100 watts. High Pressure Sodium ballasts are available as 120 volts normal and high power factor and as Tri-Tap 120,277,347 volts in 50, 70 and 100 watts.

**LAMP** All units come complete with a clear lamp. For coated lamp please state coated.



**MOUNTING** Cast aluminum base with four galvanized steel anchor bolts (1/2" x 12"). Lower body is secured to base with stainless steel screws.

**SOCKET** Medium base 4KV pulse-rated socket with a nickle-plated screw shell and a spring-loaded centre contact.

**FINISH** Standard paint finishes are Bronze, Black and White. Custom colours are available upon request.

**OPTIONS** House side cut-off and tamper proof hardware.



