

DVAKS
DVBKS
DVCS

- Precision die cast aluminum with integrated heat sinking system designed for maximum heat dissipation
- Clear polycarbonate lens is standard.
- Globe and guard options are available (see below)
- Fixture is disassembled for easy installation

CEILING MOUNT DVAKS-LED



WALL MOUNT DVBKS-LED



PENDANT DVCS-LED



- Shown with optional globe and guard (sold separately)

OPTIONAL ACCESSORIES (sold separately):



	DVAKS-LED-14W #050012	DVBKS-LED-14W #050013	DVCS-LED-14W #050014
ORDER#			
INPUT WATTS	14W	14W	14W
EQUIVALENT TO	100W Incandescent / 36W CFL Vapourproof Fixtures		
LUMEN OUTPUT	Min. 1131	Min. 1131	Min. 1131
LAMP LIFE	>50,000 hours	>50,000 hours	>50,000 hours
COLOR TEMP 5,000k	5,000k	5,000k	5,000k
VOLTAGE	120-277	120-277	120-277
WORKING TEMPERATURE	-40°C to +40°C	-40°C to +40°C	-40°C to +40°C
COLOR Rendering Index (CRI)	>70	>70	>70
DIMENSIONS	5.1"H x 4.0"W	5.4"H x 4.0"W	5.4"H x 4.0"W x 7.4"D
FINISH	Natural Aluminum	Natural Aluminum	Natural Aluminum
RATED IP65			

