



HID BELL WITH VISOR

The Bell series is ideal for use in open areas for accent and up-lighting of trees, walls, signs and building facades. The hood and heat resistant tempered clear glass with silicone gasketing, provides watertight protection.

BALLAST HOUSING Two-piece, heavy die cast aluminum with side and bottom 1/2" conduit openings. Close out plugs included. Ballast housing has a powder coat paint finish.

BELL Die cast aluminum with a powder coat paint finish.

VISOR Die cast aluminum with a heat treated tempered glass lens with silicone gasketing and a powder coat paint finish. Visor has a set screw for attachment to the bell.

MOUNTING ARM Heavy duty mounting arm with internal O-ring, locking teeth, and stainless steel screw. EZ Grip locknut matches fixture finish and can be adjusted with fingers, pliers or a screwdriver.

BALLAST All ballasts are Metal Halide Pulse start and are configured as follows, 70MH 120V NPF, 70MH 120V HPF QT and 100MH 120V HPF QT.

LAMP Lamps are not included. These fixtures are designed to take the following lamps, PAR38 Narrow Spot, Spot, Narrow Flood and Wide Flood, and ED17 lamps.



SOCKET Medium base 4KV pulse-rated socket with a nickel-plated screw shell and a spring-loaded centre contact.

FINISH Powder coat paint finish in the following colours Bronze, Black, White and Verde Green.

Catalog Code

H1

BALLAST

HN70V - 70MH 120NPF
HH70V - 70MH 120HPF QT
HH100V - 100MH 120HPF QT

FINISH

A - BRONZE
B - BLACK
W - WHITE
VG - VERDE GREEN

PLEASE NOTE LAMPS NOT INCLUDED

Dimensions

