

SIGN LIGHTING

LED

RD-L8

- UV resistant, waterproof, acrylic lens easily rotates to direct the light where needed (full 360° rotation)
- Extruded aluminum with die cast mounting hardware
- Dust and watertight connectors
- Use end caps (supplied) or interconnect multiple lights
- Standard arms extend out 18" from wall (other lengths available)

- Turns on instantly
- Easy to install
- Requires minimal maintenance. LED's are maintenance free for at least 10 years (based on a 12 hour burn)
- Maintains brightness in cold weather
- Smallest profile in this category



**ADJUSTABLE
LINEAR**
RD-L8

**AVAILABLE IN LENGTHS 2' to 8'.
LENGTHS CAN BE COMBINED TO
FORM A CONTINUOUS RUN
(See sample lengths below)**

- Lumens: 6390 per 8ft section
- Watts: 106 watts per 8ft section
Tested in Accordance to LM79/LM80
- Finish: Natural Aluminium
- Operating Temperature: -40°C to +40°C
- CRI: >70
- RATED IP65
- Approved to CSA and UL Standards

SAMPLE LENGTHS AND ORDER CODES:

Order#	Product	Volts	Length	Color Temp.
050039	RD-L8-12-LED	120-277VAC	2ft	3,600K
050040	RD-L8-14-LED	120-277VAC	4ft	3,600K
050041	RD-L8-16-LED	120-277VAC	6ft	3,600K
050042	RD-L8-18-LED	120-277VAC	8ft	3,600K
050044	RD-L8-26-LED	120-277VAC	12ft (2 x 6ft)	3,600K
050045	RD-L8-28-LED	120-277VAC	16ft (2 x 8ft)	3,600K
050046	RD-L8-46-LED	120-277VAC	10ft (1 x 4ft + 1 x 6ft)	3,600K
050048	RD-L8-68-LED	120-277VAC	14ft (1 x 6ft + 1 x 8ft)	3,600K

* Consult factory for additional configurations and color options.

• Patent pending

