

The 2HS is a fully adjustable twin head LED floodlight that can be rotated along both the vertical and horizontal axes to deliver light where needed.



APPLICATIONS

The 2HS is ideal for outdoor use on parking garages, building perimeters and entrances.

Project	
Type	
Date	
Notes	

SPECIFICATIONS

Construction

Durable aluminum construction making it suitable for outdoor use. Fixtures are rectangular in shape and have a clear tempered glass lens. The unit is fully adjustable to direct light where needed.

Voltage

120V AC, 60 Hertz

Power factor

0.9

Finish

Available in black.

LED configuration

Each fixture head comprises one high efficiency LED Chip on Board. Complete fixture delivers a minimum of 2000 lumens. The LEDs have a colour temperature of 5000K.

Electrical

Each fixture head has a power consumption of 14W making it a total of 28W (14W X 2).

Mounting

Fixture can be wall or ceiling mounted and mounts directly on to standard junction boxes.

Input Watts	28W (14W X 2)
Lumens	Min. 2000 lumens
Efficiency	71 lumens per watt
Operating Temperature	-40°C - +40°C
Certification	cCSAus
Warranty	5 Years
Colour Temperature	5000K (standard)
LED Life(L70)	50,000 hours

DIMENSIONS

