



# ORA1-LED15

LED Wall/Flood Light



## SPECIFICATIONS\*

Watts	16W
Lumens	1510
Efficacy	97lm/W
Replaces Up To	70W MH 300W Quartz
Color Temp	3000K, 4000K*, 5000K
Certification	cULus, DLC, IP65
Operating Temp	-40°C to +40°C
Voltage	120-277V, 480V in wall mount
LED Life	100,000 hours
Housing Material	Aluminum
Lens Material	Polycarbonate
Total Harmonic Distortion	18.41
Power Factor	0.912
Mounting Options	Yoke Mount, Knuckle Mount, Wall Mount



## DESCRIPTION

The ORA-LED is a fully adjustable multi-purpose fixture that replaces traditional wall packs or floods. The ORA features a sleek, elegant design with multiple mounting options.

## APPLICATIONS



Town Houses



Condos



Perimeter  
Lighting



Shopping Malls

## FEATURES

- Elegant, sleek design with a modern look.
- Fixture head may be aimed down for dark sky compliance, or aimed out as needed.
- Three mounting options available – knuckle, yoke and wall mount.


\*The above specs apply to the standard product configuration. For spec information on other product configurations please see page 4.

**NOTE:** Not all of our product configurations are qualified on the DLC QPL. To view all of our DLC qualified products please visit the DLC qualified products list at [www.designlights.org/qpl](http://www.designlights.org/qpl).


## DIMENSIONS




**Wall Mount**



**Yoke Mount**




**Knuckle Mount**




# PHOTOMETRICS

ORA1-LED15 4K MOUNTED AT 8 FEET - WALL MOUNT ORIENTATION




## ARCHITECTURAL WALL MOUNT

For architectural wall mount version order ORA knuckle mount with architectural backbox separately



### Step One




Remove screw from knuckle mount



### Step Two

Mount on bracket with wiring and tighten screw

## 480V WALL MOUNT



## SPECIFICATIONS

MODEL DESCRIPTION	VOLTAGE (V)	INPUT POWER (W)	LIGHT OUTPUT (LM)	EFFICACY (Lm/W)	THD	PF	CCT (K)	(CRI)
ORA1-LED15-B-3K-XXX-XX	120-277	16	1487	94.0	18.4	0.917	3000	72.6
ORA1-LED15-B-4K-XXX-XX	120-277	16	1510	97.2	18.4	0.912	4000	72.9
ORA1-LED15-B-5K-XXX-XX	120-277	16	1538	98.0	18.6	0.913	5000	72.6
ORA1-LED15-L-3K-XXX-XX	480	17	1748	102.7	18.4	0.929	3000	72.5
ORA1-LED15-L-4K-XXX-XX	480	17	1771	103.9	18.3	0.926	4000	73.0
ORA1-LED15-L-5K-XXX-XX	480	17	1785	104.0	18.3	0.928	5000	72.8

DLC listed as Outdoor Full-Cutoff Wall-Mounted Area Luminaire and as Architectural Flood and Spot Luminaires

### Legend

B- 120-277V, L-480V  
 4K - 4000K  
 XXX- Finish  
 XX- Mounting

## ORDERING GUIDE

<b>ORA1</b>					
WATTS	VOLTAGE	COLOR TEMP.	FINISH	MOUNTING	
LED15	B - 120 - 277V*	3K - 3000K	BRZ - BRONZE*	KN-Knuckle	
	L - 480V (Wall mount only)	4K - 4000K*		YK - Yoke	
		5K - 5000K		WMC - Wall Mount with 3 conduit entries	
				WMCB - Wall Mount for 480V	

\* Standard configuration

## FIELD INSTALLED ACCESSORIES

### CHECK THE ACCESSORIES YOU WISH TO ORDER:

- ORA1/2 WALL MOUNT with 3 Conduit Entries Bronze
- ORA1/2 Architectural Wall Mount Bracket without conduit entries Bronze