



WPTM - TRAPEZOID

MH

HPS

CFL

LED

The WPTM a wall-mounted full cut-off fixture. The WPTM has three conduit entries and the option of mounting to a junction box. The hinged lens frame allows for easy lamp replacement. Ideal for use in almost any application where light trespass or glare is a concern. For a smaller version please see WPTS.

HOUSING Precision die-cast aluminum with decorative bands. Housing has a powder coat paint finish.

LENS FRAME Precision die-cast aluminum hinged frame with a continuous rubber silicone gasket. Lens frame has a powder coat paint finish.

GLASS Tempered clear glass with a continuous silicone rubber gasket. Glass is held in place with 6 screws.

REFLECTOR Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

LEDs Thirty-two, one watt Phillips LEDs minimum 100 lumens per LED.

DRIVER 120-277 is standard optional 347 volts available.

SOCKET Medium base 4KV pulse-rated socket with a nickel-plated screw shell and a spring-loaded centre contact. White thermo plastic with integral clips for lamp retention for Compact Fluorescent models.



BALLAST For 70, 100 and 150 watt High Pressure Sodium, ballasts are Tri-Tap 120/277/347 volts. For 70, 100, 150 and 175 watt Metal Halide, ballasts are Tri-Tap 120/277/347 volts. For compact fluorescent lamps all ballasts are electronic 120-277, 347 volts for the 42 watt lamp

LAMP All units come complete with lamp.

HARDWARE All hardware is stainless steel.

FINISH Standard finish is Bronze.

OPTIONS Photocell, Tamper Proof Hardware and Quartz Restrike.

www.rabdesign.ca

Catalog Code

WPTM

LAMP

LED32, 42CFL, 70HPS,
100HPS, 150HPS, 70MH,
100MH, 150MH, 175MH

VOLTAGE

120, 277, 347, 120-277E*,
347E*

FINISH

BRZ - BRONZE

OPTIONS

TP - TAMPER PROOF
HARDWARE
PC - PHOTOCELL
QRS - QUARTZ RE-STRIKE

* ONLY AVAILABLE WITH CFL / LED OPTION

Dimensions

