

### GWL

## SLEEK, LOW PROFILE LED WALL LIGHT

Available in 4 Wattages 15W, 31W, 50W and 79W



Die cast aluminum housing and backbox

3 conduit entries in GWL1 and GWL2  
4 conduit entries in GWL3 and GWL4

Vandalproof polycarbonate lens

### features

- Die cast aluminum housing and backbox with vandal-proof polycarbonate lens
- Custom designed reflector for downward wide beam dispersion
- Stainless steel hardware
- Built-in level bubble on fixture base facilitates mounting alignment
- Replaces wallpacks from 70W MH to 250W MH

### specifications

Watts	15W	31W	50W	79W
Lumens	1674	3228	4993	7926
Efficiency	111 lumens/watt	104 lumens/watt	100 lumens/watt	101 lumens/watt
Replaces	70W MH	100W MH	150W MH	250W MH
Voltage	120 - 277V (standard), 347V (option)			
Colour Temp	5000K			
Operating Temp	-40°C to +40°C			
Finish	Bronze			
LED Life	100,000 hours			

### applications

**Ideal for building entrances and exits, offices, condominiums, facilities and schools.**

### Easy installation feature



The easy installation feature allows installer to hook fixture on top of housing and use both hands for making wiring connections