

### GWL

## SLEEK, LOW PROFILE LED WALL LIGHT

Available in 4 Wattages 15W, 31W, 50W and 79W



Die cast aluminum housing and backbox

3 conduit entries in GWL1 and GWL2  
4 conduit entries in GWL3 and GWL4

Vandalproof polycarbonate lens

### features

- Die cast aluminum housing and backbox with vandal-proof polycarbonate lens
- Custom designed reflector for downward wide beam dispersion
- Stainless steel hardware
- Built-in level bubble on fixture base facilitates mounting alignment
- Replaces wallpacks from 70W MH to 250W MH

### specifications

| Watts          | 15W                                  | 31W             | 50W             | 79W             |
|----------------|--------------------------------------|-----------------|-----------------|-----------------|
| Lumens         | 1674                                 | 3228            | 4993            | 7926            |
| Efficiency     | 111 lumens/watt                      | 104 lumens/watt | 100 lumens/watt | 101 lumens/watt |
| Replaces       | 70W MH                               | 100W MH         | 150W MH         | 250W MH         |
| Voltage        | 120 - 277V (standard), 347V (option) |                 |                 |                 |
| Colour Temp    | 5000K                                |                 |                 |                 |
| Operating Temp | -40°C to +40°C                       |                 |                 |                 |
| Finish         | Bronze                               |                 |                 |                 |
| LED Life       | 100,000 hours                        |                 |                 |                 |

### applications

**Ideal for building entrances and exits, offices, condominiums, facilities and schools.**

### Patent pending installation feature



The patent pending installation feature allows installer to hook fixture on top of housing and use both hands for making wiring connections