

## **P8RIL 42" BOLLARD**

The P8RIL bollard is suitable for landscape and pathway lighting with glare free distribution. Ideal for use in shopping malls and commercial real estate.

**LOWER BODY** 8" round extruded aluminum (.125 wall thickness) that fits over base and secured with stainless steel screws. Body has a powder coat paint finish.

**UPPER BODY 8**" round extruded aluminum held in place with stainless steel screws. For lamp replacement this section is removed. Upper body has a powder coat paint finish.

**TOP CAP** Cast aluminum held in place with stainless steel screws. Top cap has a powder coat paint finish. Upper reflector is secured to the top cap.

**OPTICS** Internal louvres made of spun aluminum, anodized, type V distribution. Internal house shield is available as 90 or 180 degrees.

**LENS** Clear acrylic

**BALLAST** All ballasts for Metal Halide are Tri-Tap 120,277,347 volts for 50, 70 and 100 watts. High Pressure Sodium ballasts are available as 120 volts normal and high power factor and as Tri-Tap 120,277,347 volts in 50, 70 and 100 watts.

**LAMP** All units come complete with a clear lamp. For coated lamp please state coated.



**SOCKET** Medium base 4KV pulse-rated socket with a nickle-plated screw shell and a spring-loaded centre contact.

**FINISH** Standard paint finishes are Bronze, Black and White, Also available is brushed and anodized. Custom colours are available upon request.

**MOUNTING** Cast aluminum base with four galvanized steel anchor bolts (1/2" x 12"). Lower body is secured to base with stainless steel screws.

**OPTIONS** House side cut-off and tamper proof hardware.





**Dimensions** 

