

The 4' LED Linear vapourproof retrofit kit is a suitable LED replacement for most existing vapourproof fixtures.



APPLICATIONS

Suitable replacement kit for FW4, VT4, VTF3, and BS100 fixtures.

Project	
Type	
Date	
Notes	

SPECIFICATIONS

Housing

Sturdy aluminum plate with highly reflective white tray. High efficiency LED driver is mounted right on the back of the unit. The retrofit kit has 2 sets of knockouts to accommodate many configurations.

Lens

Frosted lens allows for glare free illumination.

Electrical

Total system wattage of the unit is 43 watts. Each unit has high efficiency LED boards and high efficiency drivers that operate at 100V - 277V.

Dimming

0-10V dimming is available as a option.

Easy Installation

No need to re-wire, simply remove the tray with fluorescent ballast and sockets and replace with LED tray that includes driver and LED's.

Wiring

Easy installation eliminates the need to re-wire the existing fixture.

Packaging

Unit comes 2 per pack.

Input Watts	43W
Lumens	5,304
Efficiency	124 lumens per watt

Operating Temperature	-40°C to +40°C
Warranty	5 Years
Colour Temperature	4000K (standard)
Total Harmonic Distortion	20.5%
Power Factor	0.948
CRI	>80



ORDERING GUIDE

FW4	-	LED40	-		-		-		-	RETROFIT KIT
				VOLTAGE			COLOUR TEMP			OPTION
				B - 120 - 277V*			4K - 4000K*			DIM - 0-10V dimming