



The RAL-LED120 is a high efficiency area light with a Type 5 distribution. Intelligently designed, this fixture provides superior lighting performance and significant energy savings over traditional fixtures.

APPLICATIONS

Ideal for parking lots, pathways and perimeter lighting applications

Project	
Type	
Date	
Notes	

SPECIFICATIONS

Construction

Precision die cast aluminum housing with prismatic polycarbonate lens. The fixture offers superior heat sinking with continuous air-flow fins around the perimeter of the fixture.

Optics

Unit has 6 high efficiency LED Chips on Board (COB) that have an efficacy (lumens/watt) of 100. The LEDs have a colour temperature of 5000K. (4000K option also available) The operating temperature range is -40°C to +40°C. LED life is 100,000 hours.

Beam Distribution

Available in a Type 5 beam distribution. Type 3 beam distribution is also available.

Mounting

Standard unit comes with a spider mount assembly that slip fits a 2-3/8" diameter tenon.

Electrical

Total system wattage is 120W. The standard unit has a high efficiency driver that operates at 120 - 277V. 347V also available. 10KV surge protection is standard.

Finish

Standard finish is Bronze. Please consult factory for custom colour.

Options


- Photocell
- 0-10V Dimming

Warranty

5 years

Input Watts	120W
Lumens	min. 12,000
Efficacy	min. 100 lumens per watt
Equivalent to	320W MH
Beam Distribution	Type 5 (standard) Type 3 (option)
Operating Temperature	-40°C to +40°C
Certification	cULus, IP65
Warranty	5 Years
Colour Temperature	5000K (standard) 4000K (option)
LED Life	100,000 hours

DIMENSIONS



Shown with Photocell

ORDERING GUIDE

RAL	-	LED120	-		-		-		-		-	
		VOLTAGE		COLOUR TEMP		BEAM		FINISH		MOUNT		OPTIONS
		B - 120 - 277V*		5K - 5000K*		T5 - TYPE 5*		BRZ - BRONZE*		PT - POST TOP MOUNTING		DIM-0 - 10V Dimming
		C - 347V		4K - 4000K		T3 - TYPE 3		CC - CUSTOM				PC - Photocell

* Standard configuration