



APPLICATIONS

Ideal for retail buildings, schools, townhouse complexes and apartment buildings

SPECIFICATIONS


Construction

The WSDS-LED24 is a decorative fixture with a die cast aluminum housing and a clear tempered glass lens held in place with a gasket, lens frame and three stainless steel screws.

Mounting

The fixture can be wall mounted to standard junction boxes. Unit can also be surface mounted with power from conduit entry.

DIMENSIONS



| LED Configuration | |
|---------------------------|----|
| The fixture delivers a to | bt |

tal lumen output of 2,497 lumens at an efficacy of 114 lumens/ watt. The LEDs have a colour temperature of 5000K.

Electrical

Total system wattage of the unit is 22W. The standard unit has a high efficiency driver that operates at 120-277V.

Finish

Black powder coat paint finish.


The WSDS-LED is a decorative, energy efficient down light in a square cylindrical shape that can be used in a variety of commercial and residential applications.

| Project | |
|---------|--|
| Туре | |
| Date | |
| Notes | |

| Equivalent to | 100W MH | |
|---------------------------------|-----------------|--|
| Watts | 22W | |
| Lumens | 2,497 | |
| Efficacy | 114 lumens/watt | |
| | | |
| LED Life | 100,000 hours | |
| Colour Temperature | 5000K | |
| Warranty | 5 Years | |
| Operating Temperature | -40°C to +40°C | |
| Certification | cULus, DLC | |
| Power Factor | 0.9 | |
| CRI | >80 | |
| Total Harmonic Distortion | 14.15% | |



ORDERING GUIDE



WSDS-LED24 LED Wall light