




UC120-LED

Under Cabinet Light



All Sizes:



	12"	20"	40"	60"
Watts	3.67	8.38	15.92	21.47
Lumens	263	679	1,240	1,577
Efficacy (Lm/W)	71.6	81.0	77.9	73.3

SPECIFICATIONS

Color Temp	4K, 3K
Certification	cULus, IP20
Operating Temp	-20°C to +40°C
Voltage	120V (Line Voltage)
LED Life	50,000 hours
Housing Material	Aluminum
Lens Material	Polycarbonate
Accessories	90°, Straight Interconnect, Interconnect cables, 5' Power cord with Plug (with or without On/Off Switch), Wiring Compartment
Compatible Dimmers	COOPER DAL06P COOPER D106P Pass&Seymour HCL453PW
Dimming Range	100% to 2%



DESCRIPTION

The UC120-LED under cabinet light fixtures have direct 120V AC dimmable driver eliminating the need for an external power source. These fixtures are easy to install and can be used in plugin installations.

APPLICATIONS



Cove Lighting



Kitchen Cabinet



Task Lighting



Closets




Offices

FEATURES

- Line voltage under cabinet fixture with built in 120V dimming driver.
- Extruded aluminum housing with frosted lens in white finish.
- Available in lengths of 12", 20", 40" and 60".
- Available in 3,000K or 4,000K.
- 400W maximum on one run.

POLAR PLOT





HARDWIRE OPTION (SOLD SEPARATELY)

WIRING COMPARTMENT

The wiring compartment is used for hardwired applications.

- It comes with 4 knockouts for M12 X 1.5 cable glands.
- 2 cable glands are preinstalled.
- One cable gland is installed to the fixture connector and the other to the AC cable.
- The wiring compartment has a slim profile that allows for concealing beneath kitchen cabinet valences.




DIMENSIONS:





ACCESSORIES (SOLD SEPARATELY)

We offer a wide range of accessories to facilitate plugin or hardwired installations.

INTERCONNECT


	<p>STRAIGHT INTERCONNECT - (INCLUDED IN EVERY BOX)</p> <p>The straight interconnect connects fixtures and accessories in a single run.</p>
	<p>90° INTERCONNECT</p> <p>The 90° interconnect directly connects fixtures and accessories around a corner.</p>
	<p>INTERCONNECT CABLE</p> <p>Available in various lengths, the interconnect cable connects fixtures and accessories in a single run.</p> <p>AVAILABLE IN: 6" 12" 24" 36"</p>

POWER CORDS


	<p>5' POWER CORD WITH PLUG</p> <p>5' power cord with plug allows fixtures to directly connect to a power source.</p>
	<p>5' POWER CORD WITH PLUG AND ON/OFF SWITCH</p> <p>5' power cord with plug and on/off switch allows you to turn lights on/off through the switch on the power cord.</p>

DIMENSIONS


UC120-LED12




UC120-LED20




UC120-LED40




UC120-LED60




90° INTERCONNECT



STRAIGHT INTERCONNECT



5' POWER CORD WITH PLUG



MODEL SPECIFICATIONS

MODEL DESCRIPTION	VOLTAGE (V)	INPUT POWER (W)	LIGHT OUTPUT	EFFICACY (Lm/W)	PF
UC120-LED12	120	3.67	263	71.6	0.980
UC120-LED20	120	8.38	679	81.0	0.973
UC120-LED40	120	15.92	1240	77.9	0.993
UC120-LED60	120	21.47	1577	73.3	0.995

ORDERING GUIDE

UC120		
LENGTH	COLOR TEMP.	
LED12 - 12"	NW - 4000K	
LED20 - 20"	WW - 3000K	
LED40 - 40"		
LED60 - 60"		

FIELD INSTALLED ACCESSORIES:

CHECK THE ACCESSORIES YOU WISH TO ORDER:



90° Interconnect - 051389



5' Power Cord with Plug - 051395



5' Power Cord with Plug and On/Off Switch - 051396



Interconnect Cable:

6" Cable - 051391

12" Cable - 051392

24" Cable - 051393

36" Cable - 051394



Wiring Compartment with 60" cord - 051397