



## GFL LED FLOOD

**LED**

*The GFL is a rugged cast aluminum LED flood which delivers 1700 lumens. The fixture has a 1/2" NPT knuckle and comes complete with a round mounting cover plate for standard 4" junction boxes. It is ideal for doorways, entrances, sign and landscape lighting.*

**HOUSING** Precision die cast aluminum with 1/2" NPT locking swivel arm. Housing and arm have a powder coat paint finish.

**LENS** Heat and impact resistant, tempered clear glass lens.

**LEDs** Six Cree LEDs, 1700 lumens, 5000k.

**DRIVER** 120-277 volts

**MOUNTING** The GFL has a 1/2" NPT swivel arm with mounting plate. The fixture can be wall or ceiling mounted. It can also be combined with various arms as a sign light.

**FINISH** Powder coat paint finish. Standard colour is bronze. Custom colour is available as a special order.

**BEAM PATTERN** NEMA 7Hx7V

**LUMENS** 1700

**KELVIN TEMPERATURE** 5000k

**POWER CONSUMPTION** 20 Watts



**APPROVAL** cULus

**TOTAL HARMONIC DISTORTION**  
0.1598%

**POWER FACTOR** 0.992

**WORKING TEMPERATURE** -40°C TO 40°C



**WARRANTY** 5 YEARS, LEDs are rated for a minimum of 50,000 hours.

**RATING** IP65

**ACCESSORIES** Wall mounted arms.

GFL
LED20
LED / WATTAGE
120-277
VOLTAGE
FINISH
ACCESSORIES

## ACCESSORIES



MANUFACTURER:	RAB DESIGN LIGHTING INC. TORONTO, ONTARIO	
TEST #:	J300C	
TEST LAB:	LUMENTRA, INC. 160 FROBISHER DRIVE, UNIT 5 WATERLOO, ONTARIO N2L 6P6 CODE 500084-0	
ISSUE DATE:	02-02-2015	
CATALOG:	GFL-LED20-120-5K	
DESCRIPTION:	RDA LIGHTING LED FLOOD LUMINAIRE WITH WHITE REFLECTOR AND CLEAR LENS	
LAMP:	SIX WHITE LEDS. LUMEN OUTPUT = 1741 LMS.	
LAMP OUTPUT:	TOTAL LUMINAIRE LUMENS: 1744.2,	<b>ABSOLUTE PHOTOMETRY *</b>
INPUT WATTAGE:	17.85	
LUMINOUS OPENING:	POINT	
NEMA TYPE:	7 X 7	
MAX Ccd:	631.0 AT HORIZONTAL: 0°, VERTICAL: 5°	

