

LED Vapourproof





Natural aluminum is standard. Also available in other colours.



Standard natural aluminum shown.



DESCRIPTION

Available in low wattage LED configurations to maximize energy savings

Precision die cast aluminum housing

Suitable for wet locations

All RAB® Design Lighting LED luminaires are mercury and UV free

LED will deliver 70% of its initial lumen for a minimum 50,000 hours of operation

APPLICATION

Ideal for industrial applications, retail locations or any area requiring an industrial look.

* Fluorescent configurations are also available (see reverse)







EX

EXCELLENT LED LUMEN PERFORMANCE


Highly efficient heat sink maintains the junction temperature significantly below the recommended maximum ratings which allows the fixture to maintain 70% of initial lumens for at least 50,000 hours, well beyond the useful life of traditional incandescent light sources.


HIGHLY EFFICIENT LED

The Ceiling or Wall Mount LED vapourproof fixtures use fully tested high quality Philips Rebel LEDs that produce a minimum of 1458 lumens (14W).

Standard colour is a natural white 4000K, consult factory for other colour temperatures.

DIMENSIONAL DATA





ORDERING INFO example: VX1LED14-120/277-PRC-NA

SERIES	DESCRIPTION	LED	CFL	VOLTS	вох	GLOBE	FINISH
VX1	Ceiling Mount Light	14W	F13 13W Quad F26 26W Triple Tube	120 / 277	1 1/2" NPS Tapped Hub2 3/4" NPS Tapped Hub	PRC Prismatic Clear ¹ PR Red PB Blue PG Green PA Amber	NA Natural Aluminum 1 BLK Black WH White SG Silver Grey BZ Bronze
VXBR1	Wall Mount Light	14W	F13 13W Quad F26 26W Triple Tube	120 / 277	1 1/2" NPS Tapped Hub 2 3/4" NPS Tapped Hub	PRC Prismatic Clear ¹ PR Red PB Blue PG Green PA Amber	NA Natural Aluminum ¹ BLK Black WH White SG Silver Grey BZ Bronze

* Consult factory for higher wattages







¹ Standard