

## **WRUD8**

MH HPS LED

The WRUD8 is a specification grade wall mounted up down light and is slightly larger than the WRUD6. Light sources available are HPS, MH and LED. The bottom lens is removed with a quarter turn for ease of lamp replacement. The fixture also has an easy mounting system with a bracket mounted to the wall and the luminaire clips on and locked in place with two Allen screws. The WRUD8 can be used for atrium's, building entrances, columns and perimeter lighting.

**HOUSING** Extruded aluminum with a powder coat paint finish.

**LENS ASSEMBLY** Die cast aluminum with a black baffle and clear tempered glass lens.

**MOUNTING** Mounts over a standard recessed junction box.

**LED OPTION** Two LED arrays, one up, the other down light, each delivering a minimum of 4,000 lumen's per array, from the source.

**OPTICS** Narrow, Medium and Wide for LED option.

**DRIVER** Standard LED unit has a 120-277 volt driver, optional 347 volt is available.



MH OR HPS OPTION Available in 50 or 70 watt metal halide or high pressure sodium.

**BALLAST** 120 - 277V electronic ballast is standard. Please consult Customer Service for 347V option.

**FINISH** Standard finishes are bronze, black and white. Custom colours are available please consult factory.

**HARDWARE** Stainless steel

**APPROVAL** Approved to CSA standards

**RATING IP54** 

TESTED IN ACCORDANCE WITH LM-79, LM-80.

